Safety Plus World UK Limited

TY-FLOT®

Ty-Flot® | A Guardian Brand

DROPPED OBJECT PREVENTION

Product Guide



BUILT ON TRUST.

TY-FLOT®

DROPPED OBJECTS COST. TY-FLOT® SAVES.

Dropped objects don't just create hazards. They disrupt operations, delay timelines, and drive up costs. Ty-Flot® Dropped Object Prevention solutions help stop incidents before they happen by securing tools, materials, and on-person items at height. The investment is simple. The impact is immediate.

IT STAYS WITH YOU.

Working at height requires awareness of everything you carry up with you. A DOP ready worker keeps tools, PPE, and equipment secure using job ready attachments and tethers to eliminate unnecessary risk. When everything is accounted for, the work moves forward safely and efficiently.

COMPLIANCE STARTS WITH CONTROL.

Compliance in work at height environments depends on controlling hazards before they occur. OSHA regulations and ANSI ISEA 121 guidance reinforce this approach, but compliance really begins before anything falls. Ty-Flot® solutions help teams manage items at the source and reduce exposure to dropped object risks.

SECURE ABOVE = SAFE BELOW.

Effective dropped object prevention protects more than the worker. It safeguards people, equipment, and operations below. Ty-Flot® solutions create a safer work environment at height by keeping tools and materials in place without slowing productivity. The result is safer worksites and greater confidence on every job.

Ty-Flot®offers a vast range of dropped object prevention products from tethers and tool pouches to the revolutionary Quick-Switch®, the world's only hands-free tool transfer system, that streamlines the transfer of tools, without the need to disconnect the tool from an anchor.

Declaration of conformity

All products have been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by the applicable standards and regulations.

TY-FLOT®

CONTENTS

Quick-Switch® Tool Tether System

Quick-Switch® Tool Transfer Station ___ 5
Quick-Switch® Dock, Link & Transfer Keys ___ 6
Quick-Switch® Tool Pockets & Pouches ___ 7
Quick-Switch® Kits ___ 8
Quick-Switch® Tethered Tool Bucket ___ 9
Quick-Switch®Bolt Bag ___ 10

Wrist Cuffs

Cinching Wrist Cuffs _ ___ 12
Wrist Cuffs _ ___ 12
Retractable Wrist Cuffs _ ___ 13
EZ Clean Wrist Cuffs ___ 13

Tool Attachments

Tool Collar & Loop Kits ___ 15
Tool Collar Replacement Parts ___ 16
Tool Loop Replacement Parts ___ 16
Grip Fit ___ 17
Bar Clamp ___ 17
Heat Shrink ___ 18
Cold Shrink ___ 18
Cinch Loops ___ 19
Tool Tether Tape ___ 19
D-Ring Webbing ___ 20
Double D-Rings ___ 20
Wire Loop for Angle Grinder ___ 21
Wire Loop ___ 21
Drill Boot ___ 22
Tape Measure Sleeve ___ 22
Split Rings ___ 23
Anti-Vibration Tool Shackle ___ 23
Swivel Attachment ___ 24

Tool Tethers

Bungee Tool Tethers ___ 26
Heavy-Duty Tethers ___ 27
Coil Tethers ___ 28
Coil Tethers with Legs ___ 29
High Strength Tool Tethers ___ 30
Retractable Tool Tether ___ 31
Tool Tether Kits ___ 32
Tool Tethering Stations ___ 33

Tool Belts, Buckets and Pouches

Tool Belts ___ 35
Tool Buckets ___ 36
Retractable Tool Pockets ___ 37
Retractable Tool Pouches ___ 38
Belt Mount Tool Pouch ___ 38
Self Closing Tool Pouch ___ 39
Vest Pockets ___ 39

Debris Netting

Debris Netting ___ 41
Debris Netting Kits ___ 41
Pro-Knit Netting ___ 42
Zone Control Netting ___ 42

QUICK-SWITCH® TOOL TETHER SYSTEM

Quick-Switch® is an industry-first, hands-free tool tether system that streamlines secure tool transfer when working at height - without ever disconnecting the tool from its anchor. Users remain in full control with 100% tie-off, while the mechanical lock adapts to multiple tools, allowing seamless switching from belts to wrists and between hands. Innovative, interchangeable, and secure, Quick-Switch® keeps every tool safely tethered, protecting workers and equipment while helping teams stay productive at height.



Features

- **No more dangling tool tethers**
- **Reduce swinging tool hazards**
- **Low profile for snag resistance**
- **Hands-free tool switching**
- **Switch from place to place while maintaining 100% tie off**
- **Fast and easy to use**
- **Lightweight and comfortable**
- **Impact, chemical and corrosion resistant material**
- **US Patent No. 9,351,558**

Quick-Switch® Tool Transfer Station



42145



Prod. Code	Description	Packaging	Rating
42145	Quick-Switch® Tool Transfer Station*	1/pkg	6 lb (2,72 kg)
42146	Quick-Switch® Tool Transfer Station*, (2) Quick-Switch® Transfer Keys on Bungee Tethers, and (5) Quick-Switch® Links	1/pkg	6 lb (2,72 kg)
42147	Quick-Switch® Tool Transfer Station*, (2) Quick-Switch® Transfer Keys on Retractable Tethers, and (5) Quick-Switch®Links	1/pkg	6 lb (2,72 kg)

* Tools not included

Meets ANSI/ISEA 121-2023

Quick-Switch® Dock, Link and Transfer Keys

Features

- Eliminates injuries to the user as a result of dropped tools on swinging tethers or retractors
- Allows the use of multiple tools at one time without entanglement
- Keeps hands free and available for safe gripping while at height
- Tethers are reinforced with protective tube to prevent accidental damage
- Standard ANSI/ISEA 121-2023



QSWSCHCH-R



QSS-R



QSBNGEXT



RET648RPQS-R



QSDOCK-R



BRKTPCHDK-R

Part Numbers	Description	Rating
BRKTPCHDK-R	Quick-Switch®, Rotating Dock	6 lb (2,72 kg)
QSDOCK-R	Quick-Switch®, Dock	6 lb (2,72 kg)
QSBNGEXT	Quick-Switch®, Bungee Transfer Key	6 lb (2,72 kg)
RET648RPQS-R	Quick-Switch®, Retractable Transfer Key	6 lb (2,72 kg)
QSS-R	Quick-Switch®, Link & Dock (Retail Pack)	6 lb (2,72 kg)
QSWSCNCH-R	Quick-Switch®, Wrist Cuff	6 lb (2,72 kg)

Quick-Switch® Tool Pockets and Pouches



QSTLLPKT3

Features

- **Ballistic Nylon construction fits on 2 in (5 cm) belts**
- **Appropriate number of docks included with each pocket**
- **Used with a variety of tools: levels, pliers, hammers, tape measure, and more.**
- **Standard ANSI/ISEA 121-2023**



QSTAPE



QSHR

Part Numbers	Description	Rating
QSHR	Quick-Switch®, Hammer / Ratchet Pocket	6 lb (2,72 kg)
QSTAPE	Quick-Switch®, Tape Pocket	6 lb (2,72 kg)
QSTLP1	Quick-Switch®, Pocket Only, 1 Tool	6 lb (2,72 kg)
QSTLP2	Quick-Switch®, Pocket Only, 2 Tools	6 lb (2,72 kg)
QSTLP3	Quick-Switch®, Pocket Only, 3 Tools	6 lb (2,72 kg)
QSTLPKT3	Quick-Switch®, Pocket with Tape Sleeve, 3 Tools	6 lb (2,72 kg)
QSTP	Quick-Switch®, Tape Sleeve Only	6 lb (2,72 kg)

Quick-Switch® Kits

Features

- **Use your own tool pockets with the Quick-Switch® Tool Tether System**
- **Kits provide needed supplies for attaching to tools**
- **Tools less than 6 lb (2,72 kg) in weight use the Quick-Switch® Tool Tether System**
- **For heavier tools use the extension tethers**
- **US Patent No. 9,351,558**



QSSTRTKT-R

Part Numbers	Description	Rating
QSSCAFF4	Quick-Switch®, Link & Dock 4 Tool Set Up with 2 Wrist Cuffs	6 lb (2,72 kg)
QSSTRTKT-R	Quick-Switch®, Starter Kit - 4 QSS-R and 1 QSWSCNCH-R	6 lb (2,72 kg)

Quick-Switch® Tethered Tool Bucket



Features

- **Made from durable, high-strength ballistic nylon material for long-lasting performance**
- **100% tool retention during tool transfer from docks**
- **Rated up to 100 lb (45,35 kg)**

Part Numbers	Description	Bucket Weight Rating	Dock Rating
QSTTB	Quick-Switch®, Tethered Tool Bucket	100 lb (45 kg)	6 lb (2,72 kg)

Quick-Switch® Bolt Bag

Features

- **Contains bolts with two closing actions**
- **Drawstring, D-ring and snap hook**
- **Made from durable, high-strength ballistic nylon material for long-lasting performance**
- **100% tool retention during tool transfer from docks**
- **Side D-rings for tether attachment**
- **Wear on belt or attach to a rail**
- **Standard: ANSI/ISEA 121-2023**



QSBOLT

Part Numbers	Description	Dimensions	Bucket Rating	Dock Rating
QSBOLT	Quick-Switch®, Bolt Bag w/ (2) Docks & Links	10″ x 10″ x 4″ (25.4 cm x 25.4 cm x 10 cm)	25 lb (11,34 kg)	6 lb (2,72 kg)

WRIST CUFFS

Our wrist cuffs are designed as a critical component in dropped object prevention systems, providing a secure and comfortable solution for tethering tools during work at height. Engineered for durability and ease of use, these cuffs help minimize the risk of accidental drops that can lead to serious injuries, equipment damage, or operational downtime. With adjustable fits and reliable attachment points, they integrate seamlessly into safety protocols across industries such as construction, utilities, and maintenance. Whether for everyday tasks or high-risk environments, our wrist cuffs deliver dependable performance where it matters most.



Features

- **Secure tool tethering for work at height**
- **Helps prevent dropped objects, reducing injury and damage risk**
- **Adjustable, comfortable fit for all-day wear on the job**
- **High-Strength material construction holds up in construction, utility and maintenance environments**
- **Easy connect design for fast efficient tool changes**
- **Reliable anchor point for use with tool tethers in high-risk environments**

Cinching Wrist Cuffs

Features

- **Provides a single anchor point for compatible tool tethers**
- **Reinforced elastic for strength, comfort and safety**
- **Hook and loop closure**
- **One size fits most**



DRWS-R



STDCNCHOR

Part Numbers	Description	Color	Rating	QTY
DRWS-R	Wrist Cuff with Tether	Black	6 lb (2,72 kg)	1
STDCNCHOR	Wrist Cuff with Tether w/Cinching Loop, no metal	Orange	3 lb (1,36 kg)	10

Wrist Cuffs

Features

- **Unique hook and loop fastening system**
- **Stretch fabric provides superior comfort**
- **Ergonomically designed for use and comfort**
- **Steel D-ring**
- **Rated up to 6 lb (2,72 kg)**
- **One size fits most**



WCOR

Part Numbers	Description	Color	Rating	QTY
WCOR	Wrist Cuff w/ D-ring, one size	Orange	6 lb (0 to 12" Tether); 4 lb (13" to 36" Tether) 2,72 kg (0 to 30,5 cm Tether); 1,8 kg 1,8 kg (33 cm to 91,4 cm Tether)	10
WCPK	Wrist Cuff w/ D-ring, one size	Pink	6 lb (0 to 12" Tether); 4 lb (13" to 36" Tether) 2,72 kg (0 to 30,5 cm Tether); 1,8 kg 1,8 kg (33 cm to 91,4 cm Tether)	10

Retractable Wrist Cuffs



WCRETKVOR



WCRETLCKOR

Features

- **Patented full loop design**
- **Bungee fabric provides superior comfort**
- **Hook and loop closure**
- **One size fits most**
- **US Patent No. 8,210,406**

Part Numbers	Description	Color	Rating	QTY
WCRETKVOR	Wrist Cuff w/ Metal Trigger Snaps, Retractable with Kevlar® Rope	Orange	1 lb (0,45 kg)	1
WCRETKVPK	Wrist Cuff w/ Metal Trigger Snaps, Retractable with Kevlar® Rope	Pink	1 lb (0,45 kg)	1
WCRETWROR	Wrist Cuff w/ Retractable Wire	Orange	1.5 lb (0,68 kg)	1

EZ Clean Wrist Cuffs



EZLYWSPLOR

Features

- **No metal components**
- **Adjustable hook and loop wrist strap**
- **One size fits most**

Part Numbers	Description	Color	Rating	QTY
EZLYWSPLOR	Wrist Cuff, EZ Clean Wrist Tether	Orange	2 lb (0,9 kg)	10
EZLYWSPLPK	Wrist Cuff, EZ Clean Wrist Tether	Pink	2 lb (0,9 kg)	10

TY-FLOT®

TOOL ATTACHMENTS

Many tools don't have pre-existing attachment points but most tools can be made "tool tether" ready. These solutions enable users to create secure mounting interfaces that expand functionality and adaptability.

Many of the options are often designed to be interchangeable, allowing multiple tools to be used with the same setup. Depending on the application, attachment points can be configured as temporary, semi permanent of permanent-offering options for quick changes, repeated use, or long term installation.

These solutions enhance versatility, improve efficiency and security while meeting a wide ranges or operational needs.



Applications

- **Tools Without Built-In Attachment Points**
- **Construction & Industrial Work at Height**
- **Maintenance, Repair & Operations (MRO)**
- **Manufacturing & Assembly Environments**
- **Utilities, Energy & Infrastructure Work**
- **Jobsite Safety & Compliance**

TY-FLOT®

Tool Collar & Loop Kits



TL5SS

Features

- **360-degree mobility**
- **Fits a wide range of screwdrivers and shaft style tools**
- **Quick installation**
- **Stainless steel loops and rubber collars**
- **US Patent No. 8,567,290; 8,567,291**

Part Numbers	Description	Fits Diameter	Rating	Qty
TKIT3594	Tool Collar Kit TC0 and loop TL1SS	0.035″ to 0.094″ (0,88 mm to 2,38 mm)	0.75 lb (,34 kg)	25
TKIT9413	Tool Collar Kit TC1 and loop TL1SS	0.094″ to 0.13″ (2,38 mm to 3,3 mm)	0.75 lb (,34 kg)	25
TKIT1316	Tool Collar Kit TC1 and loop TL2SS	0.13″ to .016″ (3,3 mm to 4 mm)	0.75 lb (,34 kg)	25
TKIT1620	Tool Collar Kit TC2 and loop TL2SS	0.16″ to 0.20 (4 mm to 5 mm)	0.75 lb (,34 kg)	25
TKIT2026	Tool Collar Kit TC3 and loop TL3SS	0.20″ to 0.26″ (5 mm to 6,6 mm)	1.25 lb (,56 kg)	25
TKIT2630	Tool Collar Kit TC3 and loop TL4-SS	0.26″ to 0.30″ (6,6 mm to 7,6 mm)	1.25 lb (,56 kg)	25
TKIT3034	Tool Collar Kit TC4 and loop TL4SS	0.30″ to 0.34″ (7,6 mm to 8,6 mm)	1.25 lb (,56 kg)	25
TKIT3440	Tool Collar Kit TC4 and loop TL4A-SS	0.34″ to 0.40″ (8.6 mm to 1 cm)	1.25 lb (,56 kg)	25
TKIT4047	Tool Collar Kit TC5 and loop TL4ASS	0.40″ to 0.47″ (1 cm to 1,2 cm)	1.25 lb (,56 kg)	25
TKIT4755	Tool Collar Kit TC5 and loop TL5SS	0.47″ to 0.55″ (1,2 cm to 1,4 cm)	1.25 lb (,56 kg)	25
TKIT5560	Tool Collar Kit TC6 and loop TL5SS	0.55″ to 0.60″ (1,39 cm to 1,52 cm)	1.5 lb (,68 kg)	10
TKIT6072	Tool Collar Kit TC6 and loop TL5ASS	0.60″ to 0.72″ (1,52 cm to 1,90 cm)	1.5 lb (,68 kg)	10
TKIT7284	Tool Collar Kit TC6 and loop TL6SS	0.72″ to 0.84″ (1,90 cm to 2,13 cm)	3 lb (1,36 kg)	10
TKIT8496	Tool Collar Kit TC7 and loop TL6ASS	0.84″ to 0.96″ (2,13 cm to 2,43 cm)	3 lb (1,36 kg)	10
TKIT96109	Tool Collar Kit TC7 and loop TL7SS	0.96″ to 1.09″ (2,43 cm to 2,76 cm)	5 lb (2,26 kg)	10
TKIT109117	Tool Collar Kit TC7 and loop TL7ASS	1.09″ to 1.17″ (2,76 cm to 2,97 cm)	5 lb (2,26 kg)	10
TKIT117124	Tool Collar Kit TC8 and loop TL7ASS	1.17″ to 1.24″ (2,97 cm to 3,14 cm)	5 lb (2,26 kg)	10
TKIT124141	Tool Collar Kit TC8 and loop TL8SS	1.24″ to 1.41″ (3,14 cm to 3,58 cm)	5 lb (2,26 kg)	10
TKIT141161	Tool Collar Kit TC9 and loop TL8ASS	1.41″ to 1.61″ (3,58 cm to 4,1 cm)	5 lb (2,26 kg)	10
TKIT161184	Tool Collar Kit TC9 and loop TL9SS	1.61″ to 1.84″ (4,1 cm to 4,67 cm)	6 lb (2,72 kg)	10

Tool Collar Replacement Parts

Part Numbers	Description	QTY
TC0	Tool Collar, Micro	25
TC1	Tool Collar, Mini	25
TC2	Tool Collar, Small	25
TC3	Tool Collar, Medium	25
TC4	Tool Collar, Large	25
TC5	Tool Collar, XL	25
TC6	Tool Collar, XXL	10
TC7	Tool Collar, XXXL	10
TC8	Tool Collar, 1" (2,54 cm)	10
TC9	Tool Collar, 1.375" (3,46 cm)	10

Tool Loop Replacement Parts

Part Numbers	Description	QTY
TL1PL	Tool Loop, 0.14" (3,5 mm) Keyed Opening, Plastic	25
TL1SS	Tool Loop, 0.14" (3,5 mm) Keyed Opening, Stainless Steel	25
TL2PL	Tool Loop, 0.21" (5,3 mm) Keyed Opening, Plastic	25
TL2SS	Tool Loop, 0.21" (5,3 mm) Keyed opening, Stainless Steel	25
TL3PL	Tool Loop, 0.27" (6,8 mm) Keyed Opening, Plastic	25
TL3SS	Tool Loop, 0.27" (6,8 mm) Keyed Opening, Stainless Steel	25
TL4ASS	Tool Loop, 0.48" (1,21 cm) Opening, Stainless Steel	25
TL4PL	Tool Loop, 0.35" (,88 cm) Keyed Opening, Plastic	25
TL4SS	Tool Loop, 0.35" (,88 cm) Keyed Opening, Stainless Steel	25
TL5ASS	Tool Loop, 0.73" (1,85 cm) Opening, Stainless Steel	25
TL5PL	Tool Loop, 0.61" (1,54 cm) Keyed Opening, Plastic	25
TL5SS	Tool Loop, 0.61" (1,54 cm) Opening, Stainless Steel	25
TL6ASS	Tool Loop, 0.97" (2,46 cm) Opening, Stainless Steel	10
TL6SS	Tool Loop, 0.85" (2,15 cm)Opening, stainless steel	10
TL7ASS	Tool Loop, 1.26" (3,2 cm) Opening, Stainless Steel	10
TL7SS	Tool Loop, 1.1" (2,79 cm) Opening, Stainless Steel	10
TL8ASS	Tool Loop, 1.63" (4,14 cm) Keyed Opening, Stainless Steel	10
TL8SS	Tool Loop, 1.42" (3,6 cm) Opening, Stainless Steel	10
TL9SS	Tool Loop, 1.85" (4,69 cm) Opening, Stainless Steel	10

Grip Fit



Features

- **Universal swivel and three position locking D-ring**
- **Tabbed end prevents installation errors and allows for easy removal**
- **US Patent No. 9,526,322**

Part Numbers	Description	Fits Diameter	Rating	Qty
SC030BK	Grip Fit .30″ (,76 cm)	0.29″ to .4″ (0,73 cm to 1,01 cm)	6 oz (0,17 kg)	10
SC045BK	Grip Fit .45″ (1,14 cm)	0.44″ to 0.55″ (1,11 cm to 1,39 cm)	0.5 lb (0,26 kg)	10
SC056BK	Grip Fit .56″ (1,42 cm)	0.6″ to 0.7″ (1,52 cm to 1,77 cm)	1 lb (0,45 kg)	10
SC075BK	Grip Fit .75″ (1,90 cm)	0.80″ to 0.9″ (2,03 cm to 2,28 cm)	1 lb (0,45 kg)	10
SC094BK	Grip Fit .94″ (2,38 cm)	.95′ to 1.05″ (2,41 cm to 2,66 cm)	1 lb (0,45 kg)	10
SC119BK	Grip Fit 1.19″ (3,02 cm)	1.2″ to 1.3″ (3,04 cm to 3,30 cm)	1 lb (0,45 kg)	10

Bar Clamp



Features

- **D-Ring rotates 360-degrees around hexagonal and round shafts**
- **Prevents tools from dropping through grating**
- **Perfect for tools without geometry**
- **Standards: ANSI/ISEA 121-2023**
- **US Patent No. D766,058; 9,775,427; 9,801,457**

Part Numbers	Description	Fits Dimensions	Rating	Qty
CLT070	Bar Clamp 0.7″ (1,7 cm) ID	0.7″ (1,7 cm)	8 lb (3,63 kg)	5
CLT085	Bar Clamp 0.85″ (2,16 cm) ID	0.85″ (2,16 cm)	8 lb (3,63 kg)	5
CLT100	Bar Clamp 1″ (2,54 cm) ID	1″ (2,54 cm)	10 lb (4,54 kg)	5
CLT115	Bar Clamp 1.15″ (2,91 cm) ID	1.15″ (2,91 cm)	10 lb (4,54 kg)	5

Heat Shrink

Features

- **Avoid pairing confusion associated with separate heat shrink and D-rings**
- **Standards: ANSI/ISEA 121-2023**
- **US Patent No. 9,402,457; 9,339,100; D676,311**



Part Numbers	Description	Fits Diameter	Rating	Qty
TP2R34X175LPOR	Heat Shrink Attachment, High Strength, 0.75" x 1.75"(1,9 cm x 4,44 cm)	0.25" to 0.40" (0,63 cm to 1,01 cm)	1 lb (,45 kg)	10
TP2R1X175LPOR	Heat Shrink Attachment, High Strength, 1" x 1.75" (2,54 cm x 4,44 cm)	0.36" to 0.75" (0,91 cm to 1,9 cm)	2.5 lb (1,13 kg)	10
TP2R15X2LPOR	Heat Shrink Attachment, High Strength, 1.5" x 2" (3,81 cm x 5,08 cm)	0.55" to 1.25" (1,39 cm to 3,17 cm)	4 lb (1,81 kg)	10
TP2R2X2LPOR	Heat Shrink Attachment, High Strength, 2" x 2" (5,08 cm x 5,08 cm)	0.75" to 1.75" (1,9 cm to 4,44 cm)	5 lb (2,26 kg)	10
TP2R2X4LPOR	Heat Shrink Attachment, High Strength, 2" x 4" (5,08 cm x 10,16 cm)	0.75" to 1.75" (1,9 cm to 4,44 cm)	8 lb (3.62 kg)	10
TP2R275X2LPOR	Heat Shrink Attachment, High Strength, 2.75" x 2" (6,98 cm x 5,08 cm)	1.5" to 2.5" (3,81 cm to 6,35 cm)	6 lb (2,72 kg)	10
TP2R275X4LPOR	Heat Shrink Attachment, High Strength, 2.75" x 4" (6,98 cm x 10,16 cm)	1.5" to 2.5" (3,81 cm to 6,35 cm)	10 lb (4,53 kg)	10
TP2R4X4LPOR	Heat Shrink Attachment, High Strength, 4" x 4" (10,16 cm x 10,16 cm)	2" to 3.5" (5,08 cm to 8,89 cm)	5 lb (2,26 kg)	10

Cold Shrink

Features

- **No tools needed to install- just pull and go**
- **Works on tools with or without abrupt ends**
- **More resistant to abrasion and impact compared to heat shrink**
- **Standards: ANSI/ISEA 121-2023**
- **US Patent No. 9,402,457; 9,339,100; D676,311**



COLDSH275X3

Part Numbers	Description	Fits Diameter	Rating	Qty
COLDSH14X225	Cold Shrink Attachment, 1.4" X 2.25" (3,56 cm x 5,71 cm)	0.45" to 1.02" (1,143 cm to 2,59 cm)	up to 1.5 lb (,68 kg)	10
COLDSH16X25	Cold Shrink Attachment, 1.6" X 2.5" (4,06 cm x 6,35 cm)	0.55" to 1.18" (1,39 cm to 2,99 cm)	up to 3 lb (1,36 kg)	10
COLDSH16X25-R	Cold Shrink Attachment, 1.6" X 2.5" (4.06 cm x 6,35 cm)	0.55" to 1.18" (1,39 cm to 2,99 cm)	up to 3 lb (1,36 kg)	1
COLDSH1X2	Cold Shrink Attachment, 1" X 2" (2,54 cm x 5,08 cm)	0.39" to 0.63"(,99 cm to 1,60 cm)	up to 1.5 lb (,68 kg)	10
COLDSH21X275	Cold Shrink Attachment, 2.1" X 2.75" (5,33 cm x 6,98 cm)	0.075" to 1.65" (0,19 cm to 4,19 cm)	up to 4 lb (1,81 kg)	10
COLDSH21X275-R	Cold Shrink Attachment, 2.1" X 2.75" (5,33 cm x 6,98 cm)	0.075" to 1.65" (0,19 cm to 4,19 cm)	up to 4 lb (1,81 kg)	1
COLDSH275X3	Cold Shrink Attachment, 2.75" X 3" (6,98 cm x 7,62 cm)	1" to 2.48" (2,54 cm to 6,29 cm)	up to 8 lb (3,62 kg)	5
COLDSH275X3-R	Cold Shrink Attachment, 2.75" X 3" (6,98 cm x 7,62 cm)	1" to 2.48" (2,54 cm to 6,29 cm)	up to 8 lb (3,62 kg)	1
COLDSH41X35	Cold Shrink Attachment, 4.1" X 3.5" (10,41 cm x 8,89 cm)	1.65" to 3.50" (4,19 cm to 8,89 cm)	up to 10 lb (4,53 kg)	5
COLDSHKIT	KIT, Cold Shrink Attachment, 2 ea of: 1" X 2" (2,54 cm x 5,08 cm), 1.4" X 2.25" (3,56 cm x 5,71 cm), 1.6" X 2.5" (4,06 cm x 6,35 cm), 2.1" X 2.75" (5,33 cm x 6,98 cm)			Kit

Part Numbers	Description	Max. Tether Length	Rating	Qty
COLDSH41X19GRN	Cold Shrink Attachment for Angle Grinder, 4.1" X 1.9" (10,41 cm x 4,82 cm)	48" (121,92 cm)	up to 8 lb (3,62 kg)	5

Cinch Loops



TETHCNCHLPAN

Features

- **For use with hang holes or slots on tools**
- **Swivel design offers high resistance to abrasion**

Part Numbers	Description	Rating	Qty
TETHCNCHEY*	Cinch Loop Atttachment, Cord Loop & Single Eye	10 lb (4,53 kg)	10
TETHCNCHLPAN	Cinch Loop Atttachment, Webbing Loop & D-Ring	80 lb (36,28 kg)	1
TETHCNCHLPSW	Cinch Loop Atttachment, Cord Loop & Single Eye w/Swivel	10 lb (4,53 kg)	10

*Meets ANSI/ISEA 121-2023

Tool Tether Tape





MOL36RFVO

Features

- **Installs in seconds. Stretch, wrap and go**
- **Bonds to itself and leaves no residue on the tool**
- **Tape is used in conjunction to attach high strength webbing with D-ring**

Part Numbers	Description	Color	Rating	Qty
MOL36RFVB	Molecular Sealing Tape, 1" x 36 ft x .02 Thick (2,54 cm x 10,97 m x 0,5 mm)	Vibrant Blue	up to 3 lb (1,36 kg)	1
MOL36RFVO	Molecular Sealing Tape, 1" x 36 ft x .02 Thick (2,54 cm x 10,97 m x 0,5 mm)	Vibrant Orange	up to 3 lb (1,36 kg)	1
MOL36RFVP	Molecular Sealing Tape, 1" x 36 ft x .02 Thick (2,54 cm x 10,97 m x 0,5 mm)	Vibrant Pink	up to 3 lb (1,36 kg)	1

D-Ring Webbing

Features

- **High strength webbing with D-ring end**
- **Installed in conjunction with Molecular Sealing Tape**



DRSMOR
DRHDORPL

Part Numbers	Description	Color	Size	Max Tool Weight
DRSMORPL	Webbing, 4.652" L x .5" W with Plastic D-Ring	Orange	0.5" x 4.625" (1,27 cm x 11,74 cm)	5 lb (2,27 kg)
DRSMPKPL	Webbing, 4.652" L x .5" W with Plastic D-Ring	Pink	0.5" x 4.625" (1,27 cm x 11,74 cm)	1.25 lb (0,56 kg)
DRHDORPL	Heavy Duty Webbing, 4.625" L x 1" W with Plastic D-Ring	Orange	1" x 4.625" (2,54 cm x 11,74 cm)	5 lb (2,27 kg)
DRHDPKPL	Heavy Duty Webbing, 4.625" L x 1" W with Plastic D-Ring	Pink	1" x 4.625" (2,54 cm x 11,74 cm)	2 lb (0,90 kg)
DRHD12ORPL	Heavy Duty Webbing,12" L x 1" W with Plastic D-Ring	Orange	1" x 12" (2,54 cm x 30,48 cm)	12 lb (4,5 kg)
DRHD12PKPL	Heavy Duty Webbing, 12" L x 1IN W with Plastic D-Ring	Pink	1" x 12" (2,54 cm x 30,48 cm)	7 lb (3,1 kg)
DRHDOR	Heavy Duty Webbing, 4.625" L x 1" W with D-Ring	Orange	1" x 4.625" (2,54 cm x 11,74 cm)	6.5 lb (2,95 kg)
DRHDPK	Heavy Duty Webbing, 4.625" L x 1" W with D-Ring	Pink	1" x 4.625" (2,54 cm x 11,74 cm)	3 lb (1,4 kg)
DRHD12OR	Heavy Duty Webbing,, 12" L x 1" W with D-Ring	Orange	1" x 12" (2,54 cm x 30,48 cm)	12 lb (4,5 kg)
DRHD12PK	Heavy Duty Webbing,, 12" Lx 1" W with D-Ring	Pink	1" x 12" (2,54 cm x 30,48 cm)	7 lb (3,1 kg)
DRSMOR	Webbing, 0.5" x 4.625", w with D-Ring	Orange	0.5" x 4.625" (1,27 cm x 11,74 cm)	3.5 lb (1,6 kg)
DRSMPK	Webbing 4.652" L x .5" W with D-Ring	Pink	0.5" x 4.625" (1,27 cm x 11,74 cm)	1.5 lb (0,68 kg)

Double D-Rings

Features

- **Patented capture pin design will not back out with vibration**
- **The longest lasting highest weight rating attachment point option**
- **Installs in seconds with a flat head screw driver**
- **Standard: ANSI/ISEA 121-2023**
- **US Patent No. 9,038,360**



DBLD075100

Part Numbers	Description	Dimensions	Rating	Max Tether Length
DBLD0406	Double D-Ring Attachment, Small	0.4" x 0.6", (1,01 cm x 1,52 cm)	10 lb (4,54 kg)	60" (152,4 cm)
DBLD075100	Double D-Ring Attachment, Medium	0.75" x 1", (1,9 cm x 2,54 cm)	15 lb (6,80 kg)	60" (152,4 cm)
DBLD085115	Double D-Ring Attachment, Large	0.85" x 1.15", (2,15 cm x 2,92 cm)	15 lb (6,80 kg)	60" (152,4 cm)
DBLD150265	Double D-Ring Attachment, X Large	1.5" X 2.65" (3,81 cm x 6,73 cm)	25 lb (11,34 kg)	60" (152,4 cm)
DBLDKIT	Kit, Double D-Ring Attachment, 2 ea of: DBLD0406, DBLD075100, DBLD085115, DBLD150265			

Wire Loop for Angle Grinder



TLAGRN

Features

- **Includes necessary hardware to make angle grinder tether ready**
- **Quick and secure installation while maintaining full use and comfort of the handle**
- **Adaptable to most brands**
- **Opening size: 1.9 in x 1.6 in (4,8 cm x 10,6 cm)**
- **US Patent No. 10,449,662**

Part Numbers	Description	Rating	Max Tether Length	Qty
TLAGRN	Wire Loop Attachment, Angle Grinder	10 lb (4,53 kg)	48″ (1,22 m)	1

Wire Loop



Features

- **Each Wire Loop has a protected label identifying the load rating**
- **Can be used on variety of tools up to 25 lb (11,33 kg)**

Part Numbers	Description	Length	Rating	Qty
TLA65	Wire Loop Attachment	6.5″ (16,51 cm)	7 lb (3,17 kg)	1
TLA75	Wire Loop Attachment	7.5″ (19,05 cm)	7 lb (3,17 kg)	1
TLA85	Wire Loop Attachment	8.5″ (21,59 cm)	25 lb (11,33 kg)	1
TLA95	Wire Loop Attachment	9.5″ (24,13 cm)	25 lb (11,33 kg)	1
TLA105	Wire Loop Attachment	10.5″ (26,67 cm)	25 lb (11,33 kg)	1
TLA115	Wire Loop Attachment	11.5″ (29,21 cm)	25 lb (11,33 kg)	1
TLA125	Wire Loop Attachment	12.5″ (31,75 cm)	25 lb (11,33 kg)	1

Drill Boot

Features

- **Commonly used with cordless tools**
- **Quick removal for battery changes**
- **Small side pocket for storing bits**
- **Window in front and back to allow viewing of battery life**
- **Protects the battery from dropping upon accidental release**
- **Drill Boot warmer makes for longer lasting battery**
- **Max tool tether: 60 in (152,4 cm)**
- **Standard; ANSI/ISEA 121-2023**
- **US Patent No. 9,254,032; 9,833,893; D731,175**



DRLBOOTSM

Part Numbers	Description	Rating	Fits Cordless Battery Tool	Qty
DRLBOOTSM-R	Drill Boot, Small	7 lb (3 kg)	5" (12,7 cm) or smaller	1
DRLBOOTLG-R	Drill Boot, Large	7 lb (3 kg)	5" (12,7 cm) or larger	1

Tape Measure Sleeve

Features

- **Can be used with most brands of tape measures from 20 in to 35 in (50,8 cm to 88,9 cm)**
- **Max tool tether: 60 in (152,4 cm)**
- **Can be combined with an array of tool pockets or can be standalone**
- **Standard; ANSI/ISEA 121-2023**
- **US Patent No. 9,170,082; D711,753**



Part Numbers	Description	Rating	Qty
TAPESLV-R	Tape Measure Sleeve	2 lb (,9 kg)	1

Split Rings



Features

- **Easily creates attachment point with pre-drilled manufactured hang holes**
- **Fits tools with significant geometry on both ends creating a semi-permanent attachment point**
- **Pliers specifically designed to open rings effortlessly**

Part Numbers	Description	Diameter	Qty
SR04	Split Ring	0.4" (1,10 cm) Diameter	25
SR06	Split Ring	0.6" (1,52 cm) Diameter	25
SR1	Split Ring	1" (2,54 cm) Diameter	25
SR125	Split Ring	1.25" (3,17 cm) Diameter	25
SR15	Split Ring	1.5" (3,8 cm) Diameter	25
SR2	Split Ring,	2.25" (5,7 cm) Diameter	25
STDHK	Tool Attachment, Metal Trigger Snap w/ Split Ring	1.25" (3,17 cm) Diameter	25

Anti-Vibration Tool Shackle



SHKL1212LKC

Features

- **Recessed head to eliminate snag points**
- **Cost effective and more secure compared to other attachment methods**
- **Unique pin design to prevent backing out due to vibration**
- **No thread fastener required**
- **US Patent No. 9,038,360**

Part Numbers	Description	Diameter	Rating	Qty
SHKL0605LKC	Anti-Vibration Locking Tool Shackle	0.6" x 0.5" (1,5 cm x 2,27 cm)	5 lb (2,27 kg)	1
SHKL1075LKC	Anti-Vibration Locking Tool Shackle	1" x 0.75" (2,54 cm x 1,90 cm)	10 lb (4,5 kg)	1
SHKL1212LKC	Anti-Vibration Locking Tool Shackle	1.15" x 1.15" (2,92 cm x 2,92 cm)	15 lb (6,8 kg)	1
SHKL1916LKC	Anti-Vibration Locking Tool Shackle	1.9" x 1.6" (4,82 cm x 4,06 cm)	30 lb (13,6 kg)	1

Swivel Attachment

Features

- **Prevents losing the shackle pin up to 20 lb (9 kg)**
- **Swivel design to prevent tangling**
- **Easily installed with a standard crimping tool**
- **US Patent No. D676,734**



LANSHKLCR

Part Numbers	Description	Rating	Qty
LANSHKLCR	Swivel Attachment for Shackle Pins, 6" (15,2 cm) Long	10 lb (4,5 kg)	1
LANSHKLCRHD	Swivel Attachment for Shackle Pins, 6" to 13" (15,2 cm to 33 cm) Long	20 lb (9 kg)	1

TY-FLOT®

TOOL TETHERS

Tool tethers are essential safety solutions designed to prevent dropped objects when working at height or in dynamic environments. They securely connect tools to a user, structure, or anchor point, reducing the risk of injury, equipment damage, and lost productivity.

By reducing the risk of injury, equipment damage, and lost productivity, they support safer, more controlled jobsite operations.



Applications

- **Working at heights (ladders, scaffolding, lifts)**
- **Power generation, nuclear & industrial facilities**
- **Construction & maintenance sites**
- **Confined space operations**
- **Elevated platforms & rooftops**
- **Tool use over sensitive equipment or open systems**

TY-FLOT®

Bungee Tool Tethers

Features

- **Attach lighter tools to the waist or anchor heavier tools to structures**
- **High strength elastic bungee materials**
- **Specialty weaved bungee webbing**
- **Heavy-duty cord loop and cord lock for quick tool attachment**
- **Reduces impact force to body or structure**



BNGEXT1C5OR



BNGEXTRPRPOR



BNGEXTRPSSOR



BNGEXTRPSSOR

Part Numbers	Connection Ends	Rating	Length	Qty
10726	Swing Gate Carabiner & Barrel Lock Cord Loop	20 lb (9 kg)	27″ to 52″ (68,58 cm to 132 cm)	1
10736	Screw Gate & Barrel Lock Cord Loop	15 lb (6,8 kg)	27″ to 52″ (68,58 cm to 132 cm)	10
1400407	Screw Gate & Barrel Lock Cord Loop w/ Tie Back	15 lb (6,8 kg)	48″ (121,9 cm)	10
BNGEXT1C10XT	Swing Gate Carabiner & Barrel Lock Cord Loop	10 lb (4,5 kg)	34″ to 56″ (86 cm to 142 cm)	10
BNGEXT1C5OR	Screw Gate & Barrel Lock Cord	5 lb (2,26 kg)	35″ to 54″ (88,9 cm to 137 cm)	10
BNGEXT253T3T	Dual 3 Way Locking Gate Carabiner	30 lb (13,6 kg)	53″ to 63″ (153 cm to 160 cm)	1
BNGEXT253TLP-R	3 Way Locking Gate Carabiner & Loop	30 lb (13,6 kg)	53″ to 63″ (153 cm to 160 cm)	1
BNGEXT403TOLP	3 Way Locking Gate Carabiner (w/pin) & Loop	30 lb (13,6 kg)	65″ to 75″ (165 cm to 190 cm)	1
BNGEXTCC2T	Dual 2 Way Locking Gate Carabiner	20 lb (9 kg)	27″ to 52″ (17,7 cm to 132 cm)	10
BNGEXTCCSSGOR	Dual Screw Gate Carabiner	15 lb (6,8 kg)	27″ to 52″ (17,7 cm to 132 cm)	10
BNGEXTCCSSOR	Dual Swing Gate Carabiner	15 lb (6,8 kg)	27″ to 52″ (17,7 cm to 132 cm)	10
BNGEXTRPRPOR	Dual Cord Loop	15 lb (6,8 kg)	32″ to 48″ (81 cm to 121,9 cm)	10
BNGEXTRPSSGOR	Screw Gate Carabiner & Barrel Lock Cord Loop	15 lb (6,8 kg)	32″ to 48″ (81 cm to 121,9 cm)	10
BNGEXTRPSSOR	Swing Gate Carabiner & Barrel Lock Cord Loop	15 lb (6,8 kg)	32″ to 48″ (81 cm to 121,9 cm)	10
TS 18/30-15 SG-K	Swing Gate Carabiner & Loop	15 lb (6,8 kg)	32″ to 48″ (81 cm to 121,9 cm)	1

Heavy-Duty Tethers



L48403T-R

Features

- **Highest strength tool tie-off technique**
- **For large tools and equipment anchored to structures**



L72403TLP



L72803TSWLP-R

Part Numbers	Connection Ends	Rating	Length	Qty
L48803TSWLP	Heavy Duty Webbing Tether, 3 Way Locking Gate Carabiner w/Swivel & Loop	80 lb (35 kg)	48" (121,9 cm)	1
L72403TLP	Heavy Duty Webbing Tether, 3 Way Locking Gate Carabiner & Loop	40 lb (18 kg)	72" (182 cm)	1
L72803TSWLP-R	Heavy Duty Webbing Tether, 3 Way Locking Gate Carabiner w/swivel & Loop	80 lb (35 kg)	72" (182 cm)	1
L48403T-R	Heavy Duty Webbing Tether, Dual 3 Way Locking Gate Carabiners	40 lb (18 kg)	48" (121,9 cm)	1
L72WRGRND	Wire Tool Tether, 3 Way Locking Gate Carabiner & Wire Loop for Grinder	10 lb (4,5 kg)	72" (182 cm)	1

Coil Tethers

Features

- **Snag resistant design, tool tether coils up and out of the way**
- **Comparable to bungee style tethers**
- **Patented 360-degree swivel prevents tangles and increases longevity**



7000100

Part Numbers	Connection Ends	Rating	Length	Qty
CC2072	Coil Tool Tether, Dual Screw Gate Carabiner w/swivels	10 lb (4,5 kg)	20″ to 72″ (50,8 cm x 182,8 cm)	10
CC342SNP	Coil Tool Tether, Dual Metal Trigger Snaps	6 lb (2,27 kg)	3″ to 45.5″ (7,6 cm x 115,5 cm)	1
7000100	Coil Tool Tether, Screw Gate Carabiner & Screw Gate Carabiner w/Swivel	5 lb (2,26 kg)	12″ to 38″ (30,4 cm x 121,9 cm)	10

Coil Tethers with Legs



CC2350WR75LRD

Features

- **Extension legs prolongs tether life by keeping the coil outside and away from the tool pocket opening allowing smooth entry into tight pockets**
- **No restrictive connecting geometry allowing for a smooth transition in and out of the pockets**
- **Easier and quicker installation onto the tool using a secure cinching method**
- **Standard: ANSI/ISES 121-2023**
- **US Patent No. D798,042**

Part Numbers	Connection Ends	Rating	Length	Qty
CC2350WR75LRD	Coil Tool Tether, 2 Way Locking Gate Carabiner w/swivel & Loop w/Tie Back-7.5" (19 cm) Leg	3 lb (1,3 kg)	23" to 50" (58 cm to 127 cm)	10
CC2956WR14LRD	Coil Tool Tether, 2 Way Locking Gate Carabiner w/swivel & Loop w/Tie Back-14" (35,5 cm) Leg	2 lb (0,9 kg)	29" to 56" (73 cm to 142 cm)	10
CC1656WRSG	Kit, Single Tool Coil Lanyard w/Wire attachment	2 lb (0,9 kg)	16" to 56" (40 cm to 142 cm)	Kit

High Strength Tool Tethers

Features

- **Engineered to support tools 3 to 10 lb (1,3 kg to 4,5 kg) depending on model, preventing drops from height**
- **High-strength nylon webbing used for superior tensile strength, abrasion resistance, and long service life**
- **EZ-Clean coating provides smooth, non-porous outer layer resists dirt, oil, grease and contaminants-ideal for clean environments**
- **EZ-Clean coating withstands exposure to oils, UV rays, moisture, and harsh environments without degradation**
- **Metal snap hooks allow quick attachment/ detachment with secure closure to prevent accidental release**
- **Screw gate carabiner with threaded locking mechanism provide extra security for critical applications**



SNPLMS12OR



SNPS24OR



SGS36OR

Part Numbers	Connection Ends	Rating	Length	Qty
SGLMS12OR	EZ Clean Tool Tether, Dual Screw Gate	4 lb (1,8 kg)	12" (30,4 cm)	10
SGLMS24OR	EZ Clean Tool Tether, Dual Screw Gate	4 lb (1,8 kg)	24" (60,9 cm)	10
SGLMS36OR	EZ Clean Tool Tether, Dual Screw Gate	4 lb (1,8 kg)	36" (91,4 cm)	10
SNPLMS12OR	EZ Clean Tool Tether, Dual Metal Trigger Snaps w/ Swivels	4 lb (1,8 kg)	12" (30,4 cm)	10
SNPLMS24OR	EZ Clean Tool Tether, Dual Metal Trigger Snaps w/ Swivels	3 lb (1,3 kg)	24" (60,9 cm)	10
SNPLMS36OR	EZ Clean Tool Tether, Dual Metal Trigger Snaps w/ Swivels	3 lb (1,3 kg)	36" (91,4 cm)	10
SGS12OR	High Strength Webbing Tether, Dual Screw Gate	10 lb (4,5 kg)	12" (30,4 cm)	10
SGS24OR	High Strength Webbing Tether, Dual Screw Gate	10 lb (4,5 kg)	24" (60,9 cm)	10
SGS36OR	High Strength Webbing Tether, Dual Screw Gate	10 lb (4,5 kg)	36" (91,4 cm)	10
SNPS12OR	High Strength Webbing Tether, Dual Metal Trigger Snaps w/ Swivels	6 lb (2,6 kg)	12" (30,4 cm)	10
SNPS24OR	High Strength Webbing Tether, Dual Metal Trigger Snaps w/ Swivels	3 lb (1,3 kg)	24" (60,9 cm)	10
SNPS36OR	High Strength Webbing Tether, Dual Metal Trigger Snaps w/ Swivels	3 lb (1,3 kg)	36" (91,4 cm)	10

Retractable Tool Tethers

Features

- **Tether retracts when not in use**
- **Attach to belts, harness D-rings or anchoring products**
- **US Patent No. 8,919,629; 9,756,929**



HDRF810



RETPENPPOR



RETPENDB

Part Numbers	Connection Ends	Rating	Length	Qty
HDRF810	Retractable Tether, Swing Gate & Cord w/ swivel split ring	1 lb (,45 kg)	48" (121 cm)	1
HDRF810S	Retractable Tether, Swing Gate & Wire w/ swivel split ring	1 lb (,45 kg)	48" (121 cm)	1
RET348WR-R	Retractable Tether, Screw Gate & Wire w/swivel split ring	3 lb (1,3 kg)	48" (121 cm)	1
RET548RPPCH-R	Retractable Tether, Belt Loop Mount, Screw Gate w/Swivel	5 lb (26 kg)	48" (121 cm)	5
RET552RP-R	Retractable Tether, Screw Gate & Cord with Swivel Screw Gate w/swivel	5 lb (26 kg)	52" (132 cm)	1
RETDUBL	Retractable Tether, Double-Up (wire)	1.5 lb (,68 kg)	48" (121 cm)	1
RETDUBLSNP	Retractable Tether, Snap hook Double-Up (wire)	1.5 lb (,68 kg)	48" (121 cm)	1
RETPENDB	Dual Retractable, Badge & Pen Holder with Belt Clip	-	28" (60,9 cm)	1
RETPENPPOR	Dual Retractable, Marker & Pen Holder with Belt Clip	-	28" (60,9 cm)	1

Tool Tether Kits

Features

- **A variety of tool attachments in one kit**
- **Heavy-duty portable carrying case with bins and flip-top lid**
- **Contains tethering devices and tethers for smaller work activities**
- **Portable kit used to bring directly to job locations**
- **Standard heat gun required for shrink ring assembly**



LYKT3



99-11-0127

Part Number	Description
11401	Kit, Tool Tethering, Retractable Includes:1) DBLD0406, 1) DBLD075100, 1) RET552RP-R, 2) TETHCNCHEY
99-11-0125	Kit, Tool Tethering Trade Kit, Ironworker*
99-11-0126	Kit, Tool Tethering Trade Kit, Scaffold Worker*
99-11-0127	Kit, Tool Tethering Trade Kit, General Construction*
LYKT	Kit, Tool Tethering Attachment Kit & Accessories*
LYKT1	Kit, Tool Tethering, Heat Shrink Loops w/ D-Ring*
LYKT2	Kit, Tool Tethering, Basic Kit*
LYKT3	Kit, Tool Tethering, Basic Kit w/ Tool Collar & Loop*
*Individual kit contents available on ty.flot.com	

Tool Tethering Stations



TTS1SH

Features

- **High quality portable rolling cabinet with locking wheels and heavy-duty individual locking drawers**
- **A full line of tethering devices and tethers including the popular tool collars**
- **Ideal for use in heavy maintenance areas**

Part Number	Description
TTS1SH*	Tool Tethering Cabinet, Starter Station
TTS2SH*	Tool Tethering Cabinet, Pro Station

*Individual station contents available on ty-flot.com

TOOL BELTS, BUCKETS AND POUCHES

Tool belts, buckets, and pouches play a critical role in enhancing safety and efficiency in elevated or high-risk work environments.

Engineered with secure closures, reinforced materials, and load-rated attachment points, these durable storage solutions help workers keep tools organized while minimizing the risk of accidental drops and risks to personnel and equipment.

Ideal for industries like construction, utilities, and oil and gas, these products combine practicality with safety-focused innovation to ensure tools stay exactly where they're needed.



Applications

- Work at Height & Elevated Tasks
- Construction & Jobsite Tool Management
- Utilities, Energy & Infrastructure Work
- Oil and Gas & Industrial Operations
- Maintenance, Repair & Operations (MRO)
- Scaffolding, Ladders & Aerial Lifts
- Tool Organization & Secure Transport
- Dropped Object Prevention & Safety Compliance

Tool Belts

Features

- **Made from durable, high-strength ballistic nylon material for long-lasting performance**
- **Designed for dropped object prevention to enhance workplace safety**
- **Comfort-fit design reduces strain during extended wear**
- **Adjustable waist strap for a secure and customized fit**
- **Multiple tool attachment points for easy organization and access**
- **Compatible with tethers and lanyards for secure tool retention**



BELTCMFTR-R

Part Numbers	Description	Waist Sizing	Max Tether Length	Weight Rating (Belt)	Weight Rating (D-ring)	Qty
BELTCMFTR-R	Tool Belt, Comfort Fit Padded	28" to 40" Waist (71 cm-101 cm)	4 ft (121,92 cm)	*50 lb (22,67 kg)	2 lb (0,90 kg) w/ 4 ft (121,92 cm) Tether or 6 lb (2,72 kg) storage	1
BELTCMFTL-R	Tool Belt, Comfort Fit Padded	40" to 54" Waist (101 cm to 137 cm)	4 ft (121,92 cm)	*50 lb (22.67 kg)	2 lb (0,90 kg) w/ 4 ft (121,92 cm) Tether or 6 lb (2,72 kg) storage	1

*Combined total of evenly distributed pouches on the belt.

Tool Buckets

Features

- **Made from durable, high-strength ballistic nylon material for long-lasting performance**
- **Durable leather bottom for long life**
- **Featuring reflective striping**
- **Internal tethering system to prevent dropped objects**
- **Weight Rating Internal Tethers 6 lb (2,72 kg)**
- **100 lb (45,36 kg) Max Load Rating**



TB1519100BZ



TTB300BNLBZP-R

Part Numbers	Description	Color	Qty
TB1519100BZ	Tool Bucket, 15" x 19" (38 cm x 48 cm) Zipper Closure	Black	1
TTB300BNLBZP-R	Tool Bucket, 12" x 15" (30 cm x 38 cm) Zipper Closure	Black	1
TT-PPS	Plastic Bucket Sling, 5 Gallon (18,92 Liters) (Bucket not included)	Black	1

Retractable Tool Pockets



RETRPBHCL

Features

- **Made from durable, high-strength ballistic nylon material for long-lasting performance**
- **Fits up to 2 in (5 cm) belt width**
- **US Patent No. 9,038,869; 9,232,850**



RETTPBH1



RETTPBH2



RETHR

Part Numbers	Description	Reach	Rating *	Qty
RETHR	Retractable Tool Pocket for Hammer w/ 1 Retractor	48" (121,9 cm)	2 lb (0,9 kg)	1
RET4PKT	Retractable Tool Pocket, 4 Pockets w/2 Retractors	48" (121,9 cm)	2 lb (0,9 kg)	1
RETRPBH-R	Retractable Radio Pouch 1 Pocket w/1 Wire Retractor	36" (91 cm)	1.5 lb (0,68 kg)	1
RETRPBHCL	Tool Pouch For Radio, 1 Pocket w/ Coil Tether & Tether Loops	36" (91 cm)	1.5 lb (0,68 kg)	1
RETTPBH1	Retractable Tool Pocket. 1 Pocket w/1 Wire Retractor, harness adapter included	48" (121,9 cm)	2 lb (0,9 kg)	1
RETTPBH2	Retractable Tool Pocket. 1 Pocket w/2 Wire Retractors, harness adapter included	48" (121,9 cm)	2 lb (0,9 kg)	1
KITHRN1	Kit, Harness Conversion for RETTPBH1 and RETTPBH2 (2-Pieces per kit)			

* Rating is per retractor

Retractable Tool Pouches

Features

- **Two sizes hold most multi-meters, air monitors, and other portable electronics**
- **Meter retractor for electronics to prevent floor impact**
- **Designed to allow multi-meters to remain in pouch if desired**
- **Reflective striping for higher visibility**
- **US Patent No. 9,629,446**



Part Numbers	Description	Reach	Rating	Qty
RETACCSM1	Retractable Accessory Pouch w/ 1 Retractor	30" (76,2 cm)	2 lb (0,9 kg)	1
RETACCSM2	Retractable Accessory Pouch w/ 2 Retractors	36" & 30" (91,44 cm & 76,2 cm)	2 lb (0,9 kg)	1

Belt Mount Tool Pouch

Features

- **Made from durable, high-strength ballistic nylon material for long-lasting performance**
- **Buckle closure**
- **Fits up to 3 in (7,62 cm) tool belt**



TLPCH9X9

Part Numbers	Description	Size	Rating	Qty
TLPCH9X9	Tool Pouch, Belt Mount w/Internal Pocket	9" x 9" (22,8 cm x 22,8 cm)	12 lb (5,4 kg)	1

Self Closing Tool Pouch



TLPCH9X9SCL-R

Features

- **Self-closing design prevents items from unintentionally spilling**
- **Zipper top for extra security**
- **Fits up to 3 in (7.62 cm) tool belts**
- **Standards: ANSI/ISEA 121-2023**

Part Numbers	Description	Size	Rating	Qty
TLPCH9X9SCL-R	Tool Pouch, Belt Mount Self Closing	9″ x 9″ (22,8 cm x 22,8 cm)	12 lb (5,4 kg)	1

Vest Pockets



VSTPKT2



VSTPKT3

Features

- **Quick weave installation**
- **Installed directly to vest, no impediment with harness or D-ring**
- **Angled installation allows for natural movement**
- **Made to use with Molle Vest**

Part Numbers	Description	Rating	Qty
VSTPKT1	Retractable Vest Pocket Adapter with Retractor	2 lb (0.9 kg)	1
VSTPKT2	Retractable Vest/Belt Pocket for Tape Measures	2 lb (0.9 kg)	1
VSTPKT3	Retractable Vest Pocket for small tools	2 lb (0.9 kg)	1
VSTPKT4	Retractable Vest Pocket for radios	2 lb (0.9 kg)	1

TY-FLOT®

DEBRIS NETTING

Debris netting is designed to contain falling tools, materials, and debris—helping prevent dropped object incidents on construction and maintenance projects. Installed along scaffolding, guardrails, and elevated work areas, it provides a protective barrier that enhances jobsite safety while maintaining visibility and airflow.

Constructed from durable, high-strength materials, debris netting withstands demanding environments and continuous exposure to the elements. Its lightweight, flexible design allows for quick installation and secure attachment to a variety of structures, supporting efficient setup and repositioning as project needs evolve.

Debris netting delivers a reliable, scalable solution for dropped object prevention—helping crews maintain safer work zones, protect personnel and equipment, and support compliance with safety standards on active jobsites.

Applications

- **Scaffolding & Elevated Work Areas**
- **Construction & Renovation Projects**
- **Bridge, Roadway & Infrastructure Work**
- **Industrial Maintenance & Shutdowns**
- **Perimeter Protection & Debris Containment**
- **Jobsite Safety & Compliance**



Debris Netting



70001 70002

Features

- **Specialized double-strand configuration with ultraviolet coating makes netting durable and long lasting**
- **Flame retardant coating**
- **Standards: OSHA 1910; OSHA 1926 Subpart M**



70014



70015



HRCOR

Part Numbers	Description	Panel Height	Panel Length	Color	Qty
70001	Debris Net PE Roll	4′ (1,21 m)	150′ (145,72 m)	Orange	1
70002	Debris Net PE Roll	4′ (1,21 m)	150′ (145,72 m)	Blue	1
70003	Debris Net PE Roll	4′ (1,21 m)	150′ (145,72 m)	Black	1
70005	Debris Net PE Roll	5.5′ (1,67 m)	150′ (145,72 m)	Orange	1
70023	Debris Net PE Roll	5.5′ (1,67 m)	150′ (145,72 m)	Blue	1

Part Numbers	Description	Spacing	Qty
70014	Netting Plate	5′ (1,52 m) Max	1
70015	Netting Clip	2′ (0,6 m) Max	1
HRCOR	Handrail Clips	2′ (0,6 m) Max	100

Debris Netting Kits

Part Numbers	Description
70017	Kit includes (20) 70014, (50) 70015
70020	Netting Kit Includes: (1) 70002, (31) 70014, (76) 70015
70021	Netting Kit Includes: (1) 70003, (31) 70014, (76) 70015

TY-FLOT®

Pro-Knit Netting

Features

- **Specialized double-strand configuration with ultraviolet coating makes netting durable and long lasting**
- **Flame retardent coating**
- **Tighter netting than regular debris netting**
- **Reinforced border**
- **Standards: OSHA 1910; OSHA 1926 Subpart M**



70008

Part Numbers	Description	Panel Height	Panel Length	Color	Qty
70008	70 Pro-Knit MM PE	5.5′ (1,6 m)	150′ (145,72 m)	Black	1
70009	70 Pro-Knit MM PE	8.5′ (2,59 m)	150′ (145,72 m)	Black	1
70010	70 Pro-Knit MM PE	15′ (4,57 m)	150′ (145,72 m)	Black	1
70013	60 Pro-Knit MM PE	12′ (3,65 m)	300′ (91,4 m)	Black	1

Zone Control Netting

Features

- **Make temporary openings safe from falling debris**
- **Fire retardant -NFPA-701**
- **Can be used in drop or foreign material exclusion zone**
- **High visibility fluorescent orange**
- **Flexible in cold conditions**
- **Lightweight and durable**
- **Easy setup and tear down**
- **Reusable**



DN842020

Part Numbers	Description	Panel Height	Panel Length	Color	Qty
DN822005	Debris Netting (Economy Grade), Fire Retardent, 1/4″ (,63 cm) openings	4′ (1,21 m)	150′ (145,72 m)	Orange	1
DN842020	Debris Netting (Vinyl Coated), Fire Retardent, 1/8″ x 3/16″ (,31 cm x ,47 cm) openings	4′ (1,21 m)	150′ (145,72 m)	Orange	1
DN842025	Debris Netting, Fire Retardent, 5/32″ x 5/32″ (,39 cm x ,39 cm) openings	5.5′ (1,6 m)	150′ (145,72 m)	Orange	1



Safety Plus World (UK) Limited
71-75 Shelton Street, Covent Garden, London, WC2H 9JQ
info@safetyplusworld.co.uk
www.safetyplusworld.com

Call Us for more Information
+44 (0) 7710 819201